

epsilon() — Unit roundoff error (machine precision)

[Description](#) [Syntax](#) [Remarks and examples](#) [Conformability](#)
[Diagnostics](#) [Also see](#)

Description

`epsilon(x)` returns the unit roundoff error in quantities of size `abs(x)`.

Syntax

real scalar `epsilon(real scalar x)`

Remarks and examples

stata.com

On all computers on which Stata and Mata are currently implemented—which are computers following IEEE standards—`epsilon(1)` is $1.0X^{-34}$, or about $2.22045e-16$. This is the smallest amount by which a real number can differ from 1.

`epsilon(x)` is `abs(x)*epsilon(1)`. This is an approximation of the smallest amount by which a real number can differ from `x`. The approximation is exact at integer powers of 2.

Conformability

`epsilon(x)`:

x: 1×1
result: 1×1

Diagnostics

`epsilon(x)` returns `.` if `x` is missing.

Also see

[M-5] [edittozero\(\)](#) — Edit matrix for roundoff error (zeros)

[M-5] [mindouble\(\)](#) — Minimum and maximum nonmissing value

[M-4] [Utility](#) — Matrix utility functions

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).