

valofexternal() — Obtain value of external global

Description Syntax Remarks and examples Conformability
 Diagnostics Also see

Description

`valofexternal(name)` returns the contents of the external global matrix, vector, or scalar whose name is specified by *name*; it returns `J(0,0,.)` if the external global is not found.

Also see [Linking to external globals](#) in [M-2] **Declarations**.

Syntax

transmorphic matrix `valofexternal(string scalar name)`

Remarks and examples

stata.com

Also see [M-5] **findexternal()**. Rather than returning a pointer to the external global, as does `findexternal()`, `valofexternal()` returns the contents of the external global. This is useful when the external global contains a scalar:

```
tol = valofexternal("tolerance")
if (tol==J(0,0,.)) tol = 1e-6
```

Using `findexternal()`, one alternative would be

```
if ((p = findexternal("tolerance"))==NULL) tol = 1e-6
else tol = *p
```

For efficiency reasons, use of `valofexternal()` should be avoided with nonscalar objects; see [M-5] **findexternal()**.

Conformability

`valofexternal(name)`:

<i>name</i> :	1×1
<i>result</i> :	$r \times c$ or 0×0 if not found

Diagnostics

`valofexternal()` aborts with error if *name* contains an invalid name.

`valofexternal(name)` returns `J(0,0,.)` if *name* does not exist.

Also see

[M-5] [findexternal\(\)](#) — Find, create, and remove external globals

[M-4] [Programming](#) — Programming functions

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).