

estat lcpob — Latent class marginal probabilities

Description	Menu	Syntax	Options
Remarks and examples	Stored results	Also see	

Description

`estat lcpob` is for use after `gsem` but not `sem`.

`estat lcpob` reports a table of the marginal predicted latent class probabilities.

`marginsplot` can be used after `estat lcpob` to plot the marginal predicted latent class probabilities.

Menu

Statistics > LCA (latent class analysis) > Class marginal probabilities

Syntax

```
estat lcpob [ , options ]
```

<i>options</i>	Description
<code>classpr</code>	latent class probability; the default
<code>classposteriorpr</code>	posterior latent class probability
<code>nose</code>	do not estimate SEs
<code>post</code>	post margins and their VCE as estimation results
<code>display_options</code>	control column formats, row spacing, and line width

`collect` is allowed; see [U] 11.1.10 [Prefix commands](#).

Options

`classpr`, the default, calculates marginal predicted probabilities for each latent class.

`classposteriorpr` calculates marginal predicted posterior probabilities for each latent class. The posterior probabilities are a function of the latent class predictors and the fitted outcome densities.

`nose` suppresses calculation of the VCE and standard errors.

`post` causes `estat lcpob` to behave like a Stata estimation (e-class) command. `estat lcpob` posts the vector of estimated margins along with the estimated variance–covariance matrix to `e()`, so you can treat the estimated margins just as you would results from any other estimation command.

`display_options`: `vsquish`, `fvwrap(#)`, `fvwrapon(style)`, `cformat(%fmt)`, `pformat(%fmt)`, `sformat(%fmt)`, and `nolstretch`.

Remarks and examples

See [\[SEM\] Example 50g](#), [\[SEM\] Example 53g](#), and [\[SEM\] Example 54g](#).

Stored results

`estat lcprob` stores the following in `r()`:

Scalars

`r(N)` number of observations

Macros

`r(title)` title in output

`r(classposteriorpr)` `classposteriorpr`

Matrices

`r(b)` estimates

`r(V)` variance–covariance matrix of the estimates

`r(table)` matrix containing the margins with their standard errors, test statistics, *p*-values, and confidence intervals

`estat lcprob` with the `post` option also stores the following in `e()`:

Scalars

`e(N)` number of observations

Macros

`e(title)` title in output

`e(classposteriorpr)` `classposteriorpr`

`e(properties)` `b V`

Matrices

`e(b)` estimates

`e(V)` variance–covariance matrix of the estimates

Also see

[\[SEM\] gsem](#) — Generalized structural equation model estimation command

[\[SEM\] gsem postestimation](#) — Postestimation tools for `gsem`

[\[SEM\] Example 50g](#) — Latent class model

[\[SEM\] Example 53g](#) — Finite mixture Poisson regression

[\[SEM\] Example 54g](#) — Finite mixture Poisson regression, multiple responses

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).